



INSTALLATION

STINGER VENTED TRAP DOOR

8498

FITS: ALL STANDARD HYPERCHARGER BODIES - LATE, EARLY AND EFI

PARTS INCLUDED

- 1 Stinger Vented Trap Door — Chrome
- 1 Flat Filter Cage
- 1 Cup Filter Cage
- 1 Black Foam Air Filter
- 4 10-24 X 3/8" Socket Head Cap Screws
- 1 Installation Instruction

Please read and understand entire instructions before starting installation.

THANK YOU FOR CHOOSING KÜRYAKYN!

IN ORDER TO PROTECT YOU AND OTHERS FROM POSSIBLE INJURY AND/OR PROPERTY DAMAGE OR LOSS, PLEASE PAY CLOSE ATTENTION TO ALL INSTRUCTIONS, WARNINGS, CAUTIONS AND ATTENTION NOTES REGARDING THE USE AND CARE OF THIS PRODUCT.

TOOLS SUGGESTED

1/8" Hex Key wrench

STRICTLY OBSERVE THE FOLLOWING GUIDELINES IN ORDER TO USE THE PRODUCT PROPERLY AND AVOID POTENTIALLY DANGEROUS ACCIDENTS.

PROCEDURE

STEP 1 Use a 1/8" hex key wrench; remove the four button head cap screws from the trap door on the hyper.

STEP 2 Remove the trap door and the trap door gasket.

STEP 3 Set the filter assembly in place with the cup section of the filter cage inside the Hypercharger. Hold the Stinger Vented Trap Door in place and line up the mounting holes in the Stinger, the filter and the Hypercharger. Secure the Stinger and filter to the Hypercharger using the supplied 10-24 X 3/8" Socket Head Cap Screws and tighten.

FILTER CLEANING TIPS

- Separate the two halves of the filter cage to remove the filter.
- Using a mild soap and warm water solution and let the filter soak for a short time. Rinse thoroughly and allow to air dry, then re-oil with foam filter oil. Do not use high-pressure water to wash the filter. Do not use compressed air to dry the filter. K&N Filter Care Kit, Kuryakyn P/N 85 may also be used.

Ride On!

CUSTOMER SERVICE
877.370.3604 (toll free)

INSTALLATION QUESTIONS
techsupport@kuryakyn.com
or call 715.247.2983

LIMITED WARRANTY

Kuryakyn warrants that any Kuryakyn products sold hereunder, shall be free of defects in materials and workmanship for a period of one (1) year from the date of purchase by the consumer excepting the following provisions:

- Kuryakyn shall have no obligation in the event the customer is unable to provide a receipt showing the date the customer purchased the product(s).
- The product must be properly installed, maintained and operated under normal conditions.
- Kuryakyn makes no warranty, expressed or implied, with respect to any gold plated products.
- Kuryakyn shall not be liable for any consequential and incidental damages, including labor and paint, resulting from failure of a Kuryakyn product, failure to deliver, delay in delivery, delivery in nonconforming condition, or for any breach of contract or duty between Kuryakyn and a customer.
- Kuryakyn products are often intended for use in specific applications. Kuryakyn makes no warranty if a Kuryakyn product is used in applications other than intended.
- Kuryakyn electrical products are warranted for one (1) year from the date of purchase by the consumer. Components of Kuryakyn products containing L.E.D.s will be warranted for defects in materials and workmanship for 3 years from the date of purchase.
- Kuryakyn makes no warranty of any kind in regard to other manufacturer's products distributed by Kuryakyn. Kuryakyn will pass on all warranties made by the manufacturer and where possible, will expedite the claim on behalf of the customer, but ultimately, responsibility for disposition of the warranty claim lies with the manufacturer.

ABOUT OUR CATALOG

You'll find all our innovations for H-D, GL and Metric Cruisers in our annual catalogs. Order online today—select the "CATALOGS" icon. Each Kuryakyn® product comes with a Proof-of-Purchase good for a complimentary catalog. Details in packaging.

Be sure to ask your local dealer about other Kuryakyn® products, the motorcycle parts and accessories designed for riders by riders.

©2005 Kuryakyn USA® All Rights reserved.



kuryakyn.com