



CATCH TANK FOR BLUE GRASS BREATHER 9931

FITS ALL MODELS USING THE BLUEGRASS BREATHER KIT, P/N 9930 OR 9932.

PART #	INCLUDED
609931	1 Catch Tank Assembly, including:
	1 LIL Tank, Chrome
	1 LIL Tank Inlet Rib, Chrome
	1 Rubber Gasket
	1 Vent Pipe
	1 Oil-Safe Sponge
909931	1 Hardware Kit, including:
	1 0.50 ID x 36" Hose
	1 SST Universal Strap
	1 5/16 – 18 x 1" SHCS Stainless Fastener
	1 5/16 – 18 x 3/4" SHCS Stainless Fastener
	2 5/16 – 18 High Crown Acorn Nut
	2 5/16" Split Lock Washer
	2 5/16" Flat Washer
	2 3/4" Wire Clamp
	4 6" Black Cable Tie
309931	1 Installation Instructions

Please read and understand entire instructions before starting installation.

THANK YOU FOR CHOOSING KÜRYAKYN!

PLEASE NOTE

It is the installers' responsibility to make sure all fasteners (including pre-assembled) are tightened before operation of motorcycle. Kuryakyn will not warranty components that are lost due to improper installation. Periodic maintenance may be required.

TOOLS SUGGESTED

Allen wrenches

NOTE: The universal catch tank can be mounted in a variety of ways. This procedure outlines two potential ways to mount the catch tank; always orient the catch tank upright with the vent slots at the top.

IMPORTANT GUIDELINES

- Always orient the catch tank upright with the vent slots on top.
- Be careful not to lose the o-ring sealing the tank to the cap.
- When installing, tighten the tank to the cap securely using an Allen wrench in the hex cutout in the bottom of the tank.
- Check and empty the catch tank regularly to avoid potential overflow. Regularly inspect the vents for weeping oil. If you find weeping oil, clean the sponge. Unscrew the tank from the cap using an Allen wrench in the bottom of the tank. Be careful not to lose the o-ring that seals the tank to the top cap. Squeeze the excess oil from the sponge; you may wash it with soap and warm water if it is dirty. Be sure to rinse the sponge thoroughly and squeeze out any excess water. Reinstall the tank to the cap in the reverse order.

CUSTOMER SERVICE

877.370.3604 (toll free)

INSTALLATION QUESTIONS

techsupport@kuryakyn.com
or call 715.247.2983

LIMITED WARRANTY

Kuryakyn warrants that any Kuryakyn products sold hereunder, shall be free of defects in materials and workmanship for a period of one (1) year from the date of purchase by the consumer excepting the following provisions:

- Kuryakyn shall have no obligation in the event the customer is unable to provide a receipt showing the date the customer purchased the product(s).
- The product must be properly installed, maintained and operated under normal conditions.
- Kuryakyn makes no warranty, expressed or implied, with respect to any gold plated products.
- Kuryakyn shall not be liable for any consequential and incidental damages, including labor and paint, resulting from failure of a Kuryakyn product, failure to deliver, delay in delivery, delivery in nonconforming condition, or for any breach of contract or duty between Kuryakyn and a customer.
- Kuryakyn products are often intended for use in specific applications. Kuryakyn makes no warranty if a Kuryakyn product is used in applications other than intended.
- Kuryakyn electrical products are warranted for one (1) year from the date of purchase by the consumer. Components of Kuryakyn products containing L.E.D.s will be warranted for defects in materials and workmanship for 3 years from the date of purchase.
- Kuryakyn makes no warranty of any kind in regard to other manufacturer's products distributed by Kuryakyn. Kuryakyn will pass on all warranties made by the manufacturer and where possible, will expedite the claim on behalf of the customer, but ultimately, responsibility for disposition of the warranty claim lies with the manufacturer.

ABOUT OUR CATALOG

You'll find all our innovations for H-D, GL and Metric Cruisers in our annual catalogs. Order online today—select the "CATALOGS" icon. Each Kuryakyn™ product comes with a Proof-of-Purchase good for a complimentary catalog. Details in packaging.

Be sure to ask your local dealer about other Kuryakyn products, the motorcycle parts and accessories designed for riders by riders.

©2005 Kuryakyn USA™ All Rights reserved.



INSTALLATION SUGGESTIONS

WARNING! Never mount the catch tank where an overflow could deposit oil directly onto a tire. This could cause loss of control while operating the motorcycle.

- The catch tank can be mounted with either the supplied universal strap or a P-Clamp (sold separately). PIC.1 shows the catch tank mounted to the horn bracket using the supplied universal strap.
- PIC.2 shows the tank mounted to the frame using a Kuryakyn P-Clamp (sold separately). P-Clamps are available in a variety of sizes to cover many applications.

Ride On!

Kuryakyn

PIC.1



UNIVERSAL STRAP

PIC.2



P-CLAMP

PAGE

2